vtech

Product Release Notice ErisTerminal[®] 1.1.4.0 Firmware

Release Date: May 2016

This document contains the release notes for VTech ErisTerminal version 1.1.4.0. This upgrade release, affecting the VSP715, VSP725 and VSP735 SIP Desksets, the VSP600 SIP DECT Base Station and Cordless Handset and the VCS754 Conference Phone, includes significant enhancements; therefore, users of previous ErisTerminal releases are encouraged to upgrade. The following topics are detailed below.

What's new? Recent changes Configuration file parameter changes How to upgrade Version compatibility Manuals Product support

What's new?

No new features have been added for the release of 1.1.4.0.

Recent changes

All products:

Description	Reference Number
Passwords entered on the WebUI are now immediately masked.	#2701
To minimize bootup time in non-LLDP environments, LLDP-MED timeout changed to 10 seconds.	#2818
LLDP-MED is enabled by default for all models.	#3092
Added ability to configure BLF remote pickup using extension numbers (VSP600/600A not affected).	#2603, #2620
For products with smaller LCDs, added the ability to toggle between an incoming caller's Display Name and User ID (VSP735, VSP600/600A not affected).	#2821
Improved password security, including alerts when default passwords are still in use.	#2918, #2919
Added parameter to enable/disable periodic alert for insecure password.	#3088
Fixed issue with INVITE transactions to enable faster cancellation of calls to unavailable servers.	#2728

Page | 1

businessphones.vtech.com/

© 2016 VTech Communications, Inc.

ErisTerminal®, ErisStation®, ErisBusinessSystem™ and Orbitlink Wireless Technology™ are trademarks of VTech Communications, Inc. All other marks are the property of their respective owners.

All rights reserved. $\mathsf{VTech}{}^{\texttt{R}}$ is a registered trademark of VTech Holdings Ltd.

vtech

Added call_rejection_response_code parameter to support codes 480, 486 (default) and 603.	#2854
Updated default time and date to 01-03-2016 00:00.	#2877
Introduced intrusion detection to the WebUI. WebUI will lock out users for five minutes after three consecutive failed login attempts	#2897
For security reasons, added WebUI message reminding users to close the browser after a configuration session.	#2902

VSP715, VSP725 and VSP735:

Description	Reference Number
Fixed issue with calling a BLF-monitored extension that previously received a parked call.	#3407

VSP600/601:

Description	Reference Number
Verified that VSP600 Base Station supports registration of the VSP608 Deskset.	#2881

VCS	7	54	:

Description	Reference Number
Fixed issue with Program Dial soft key appearing in Held mode after having been disabled.	#2856

Configuration file parameter changes

The following configuration file parameters have been introduced or modified in 1.1.4.0.

sip_account.x.call_rejection_response_code New parameter
--

How to upgrade

Please refer to the Administrator and Provisioning Manual for your ErisTerminal product, available here.

Version compatibility

Version 1.1.4.0 is compatible with previous versions.

Manuals

For more information on the features described in this document, please reference the manuals and technical documents located here: <u>http://businessphones.vtech.com/support/manuals</u>

Product support

For additional questions, please contact the VTech Business Phones team. Contact information is available here: <u>http://businessphones.vtech.com/support/contact-us</u>

Page | 2

businessphones.vtech.com/

© 2016 VTech Communications, Inc.

ErisTerminal®, ErisStation®, ErisBusinessSystem™ and Orbitlink Wireless Technology™ are trademarks of VTech Communications, Inc. All other marks are the property of their respective owners.

All rights reserved. VTech $\ensuremath{\mathbb{R}}$ is a registered trademark of VTech Holdings Ltd.