

HIGH PERFORMANCE

ULTRA-STYLISH CHIC DESIGN

SMALL FOOTPRINT

Adds a touch of elegance to guest rooms





PMX-S5410 1-Line SIP Cordless Phone

PMX-S5420 2-Line SIP Cordless Phone



Champagne Gold/Black



Silver/Black

KEY FEATURES

- High quality 3" LCD touchscreen with 65K colours and multi-language user-friendly interface
- Ultra-stylish and chic. Small footprint
- Anti-bacterial plastic inhibits 99.9% of bacteria growth - protect both guests and housekeeping staff from germs
- Real time clock, room number, and hotel logo programming available
- LCD automatic OFF mode when idle to save energy
- Simple handset registration
- Compatible with all major PBXs

CORDLESS PHONE FEATURES

- Expandable cordless telephone system - supports up to 4 handsets
- Answer a call by simply picking up the handset from the charger for quick response
- Multi-level volume control
- Backlit handset dial pad for better visibility in low light environments
- Speakerphone and Hold key on handset
- Handset battery life - Up to 4 hours talk time with 4 days standby
- Quickly locate all cordless handsets in the system using the Find Handset key

* Some features may be revised subject to final design of hardware and software platform.



PRODUCT RANGE

Product Type	Model	Champagne Gold/Black	Silver/Black
<u>Standard Cordless Handset and Base</u>	PMX-S5410 (1 Line) PMX-S5420 (2 Lines)		
<u>Hidden Base with Cordless Handset and Charger</u>	PMX-S5410 HC and PMX-S5410-HID (1 Line) PMX-S5420 HC and PMX-S5420-HID (2 Lines)		
	PMX-S5410 HC-S and PMX-S5410-HID (1 Line) PMX-S5420 HC-S and PMX-S5420-HID (2 Lines)		
<u>Accessory Cordless Handset and Charger</u>	PMX-S5410 HC (1 Line) PMX-S5420 HC (2 Lines)		
	PMX-S5410 HC-S (1 Line) PMX-S5420 HC-S (2 Lines)		



SPECIFICATIONS

Standard Colours: Champagne Gold/Black, Silver/Black
 Radio Frequency Baseband: Available in DECT 1.8GHz and DECT 1.9GHz
 Message Waiting Signal Type: SIP RFC 3261
 Power Source:
 Main Base - 5V DC External Power/PoE
 Charger Unit - 5V DC External Power/PoE
 Hidden Base - 5V DC External Power/PoE
 Humidity: 65% ± 20%
 Temperature: 35°C ± 10°C

CERTIFICATES

- FCC Part 15 Subpart B
- FCC Part 68
- RoHS Compliant
- CE
- ETL



DIMENSION & WEIGHT

	DEVICE DIMENSION			CARGO DIMENSION & WEIGHT				
	Length	Width	Height	Length	Width	Height	Quantity	Weight
PMX-S5410/PMX-S5420 (Handset + Base)	155mm	90mm	200mm	584mm	254mm	214mm	12 pcs/carton	7132g
PMX-S5410 HC/PMX-S5420 HC (Handset + Charger)	155mm	90mm	200mm	584mm	254mm	214mm	12 pcs/carton	7132g
PMX-S5410 HC-S/PMX-S5420 HC-S (Handset + Charger)	118mm	103mm	200mm	584mm	254mm	214mm	12 pcs/carton	6376g
PMX-S5410-HID/PMX-S5420-HID (Hidden Base)	254mm	156mm	35mm	538mm	484mm	185mm	10 pcs/carton	6016

CORDS

3 metre standard LAN cable with RJ45 connectors